

Gravity Gear Kernmantle 10.5mm

N01Q4019....

The Gravity Gear Specialised range includes CE certified high access kernmantle rope manufactured for use in Rope Access, Team Rescue and Rope Rigging.

All Gravity Gear Ropes are durable and tested to conform to local (SABS) and international standards (EN 1891:1998 / AS 4142.3 1993) of working at height and fall protection equipment.

FEATURES & BENEFITS

- High static strength
- Low elongation
- Knotability factor
- Low sheath slippage
- Sheath with 32 SPINDLE
- Fall arrest peak force accordance
- Join free packaging – 50m to 200m

INDUSTRIES

- Industrial – refineries, chemical
- Wind turbine towers
- Construction
- Mining
- Cleaning services
- And many more...



Ref.	Product name	Length	Weight	Static strength	Static strength w/ figure 8 knot	No. of factor 1 falls (100kg)	Fall factor 0.3 impact force	Static elongation	Sheath slippage	Sheath	Shrinkage in water	Material
			g/m	kN	kN		kN	50/150 kg (%)	mm	%	%	
4019	Gravity Gear 10.5 mm	50 m	71	29	15	≥5	5.2	4.3	27	43.1	2.7	Polyester
		100 m										
		150 m										
		200 m										

DIRECTORS: GD FORSTER, AF NEL, R GRIESEL CA(SA), BJ SASS